

JYL-NMT7032



Application:

- Supply Chain Management
- Process Control & Factory Automation
- Production management
- Machine Identification
- Inventory Control
- Patrol System

Highlights:


On Metal tag is designed for industrial applications on metal, The inner antimetal layer stopped the interference of the metal. The tag is fixed by screw, it is very steady in industrial environment. To handle very harsh outdoor environment, the tag is filed with epoxy, so it is completely resist water and dust.

Tag Spec.:

Housing	Nylon/ABS material + Filling epoxy	Operating Frequency:	LF, HF, UHF for optionl
Dimension:	70 x 32.5 x 8mm	Approx Weight:	18g / 5g
Thickness:	5.3mm / 8mm	Color:	Black / Yellow
Store temperature:	-30°C ~ +75°C	Protection:	IP68
Working temperature:	-25°C ~ +60°C	Resistance:	Harsh out door environment, Water/dust proof

Optional :

Coding:	Chip Encoding
Customized Logo Printing:	Laser engrave
ID Number Printing:	Laser engrave
Data Retention	10 years
Warranty:	1 year



The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.